SPILL PRIORITY LIST – April 1 through no later than August 31.

The Spill Priority List (SPL) defines how _Lack of Load_ spill will be distributed to projects in order to manage TDG on a system-wide basis. In the event of spill due to Lack of Load, spill will occur at projects in the following sequential priority order at the spill level defined for incrementally higher levels of TDG.

Level	Priority Order	Project	TDG (%)	_Example_ Spill Level (kcfs)
LEVEL 1 **State TDG Standard** [1] **("Gas Cap")** _In Level 1, Lack of Load spill will be allocated to projects that are not already spilling to the gas cap for FOP spill (i.e., projects that spill to the gas cap for FOP spill will be skipped over)._	1	LWG	120% / 115%	To Be Determined
	2	LGS	120% / 115%	To Be Determined
	3	LMN	120% / 115%	To Be Determined
	4	IHR	120% / 115%	To Be Determined
	5	MCN	120% / 115%	To Be Determined
	6	JDA	120% / 115%	To Be Determined
	7	TDA	120% / 115%	To Be Determined
	8	BON	120% / na	To Be Determined
	9	CHJ	110%	25
	10	GCL	110%	Outlet Tubes=0; Drum Gates=5
	11	DWR	110%	35% of project outflow
LEVEL 2	12	LWG	120%	45
	13	LGS	120%	52
	14	LMN	120%	44
	15	IHR	120%	90
	16	MCN	120%	146
	17	JDA	120%	146
	18	TDA	120%	135
	19	BON	120%	120
	20	CHJ	120% / 115%	60
	21	GCL	115%	Outlet Tubes=5; Drum Gates=15
LEVEL 3	22	LWG	122%	52
	23	LGS	122%	59
	24	LMN	122%	60
	25	IHR	122%	95
	26	MCN	122%	152
	27	JDA	122%	177
	28	TDA	122%	160
	29	BON	122%	160
	30	CHJ	120%	100
	31	GCL	120%	Outlet Tubes=15; Drum Gates=40

---

[1] The State TDG standard (also referred to as "Gas Cap") is ≤110% in all project tailraces, except during spill for fish passage, Apr 1–Aug 31, when the standard at the lower Snake and lower Columbia River projects is modified to ≤120% in the tailrace and ≤115% in the next downstream forebay. Daily gas cap spill levels ("spill caps") are posted online at: pweb.crohms.org/tmt/documents/ops/spill/caps/

Level	Priority Order	Project	TDG (%)	*Example* Spill Level (kcfs)
LEVELS 4 and up	Same Priority Order as Level 3			